

LABdex



Online Conductivity Controller LX102OCC

Email: info@labdex.com **website:** www.labdex.com

Description

Online conductivity controller LX102OCC is a portable unit with automatic temperature compensation (ATC) that provides highly accurate results. It simultaneously displays measured parameters such as conductivity, TDS, temperature, date and time. Measures primary controlling parameter conductivity of solutions. Alarm output according to the upper and low limits of conductivity.

Specifications

Conductivity range	0 ~ 20 mS/cm
Auto reversible conductivity range	0 ~ 20 μ S/cm 0 ~ 200 μ S/cm 0 ~ 2000 μ S/cm 0 ~ 20 mS/cm
Conductivity electrode	Process conductivity electrode (LX4202)
Electrode cell constant	10
Temperature compensation	0 ~ 60 °C
Ambient Temperature	0 ~ 50 °C
Humidity	≤ 85 %
Alarm output	220 V / 6 A
Current output	4 mA ~ 20 mA Isolated DC output (Max Load : 750 Ω)
Power	110 V 220 V 240 V
Dimensions	Frame dimensions : 96 mm × 96 mm Panel dimensions : 91 mm × 91 mm Depth : 100 mm

Features

- ˆ RS-232 interface
- ˆ Alarm output according to the upper and low limits of conductivity
- ˆ Automatic reversible measurement range
- ˆ Auto adjustable to zero
- ˆ Pipe-thread connecting electrode

- Easy calibration
- Came with 4-20mA

Applications

- Used in chemical, pharmaceutical, food industries and medical laboratories. Also widely used for laboratory analysis, soil and water quality tests, etc.

Electrode Specifications

Conductivity electrode	Process conductivity electrode (LX4202)
Material	Graphite
Cell constant	5
Measurement range	2 ~ 20m S/cm
Operating temperature	5 ~ 60 °C
Thread size	3/4" NPT
Cable length	5 m
Electrode length	147 mm
Shaft material	PPS



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com